.32

* LEVEL MASTER STUMP SUPPORTING 9m² OF ROOF LOAD AND 9m² OF FLOOR LOAD 3m OF WALL FRAME 2.4m HIGH IN AN N3 WIND AREA.

$$\begin{aligned}\text{DOWNWARDS} &= 9\text{m}^2 \times 0.78\text{kN/m}^2 \text{ (roof)} + \\ &\quad 9\text{m}^2 \times 2.85\text{kN/m}^2 \text{ (floor)} + \\ &\quad 3\text{m wall} \times 2.4 \text{ high} \times 0.42\text{kN/m}^2 \text{ (wall)} \\ &= 35.7 \text{ kN total.}\end{aligned}$$

N3 WIND UPLIFT= $9\text{m}^2 \times 1.01\text{kN/m}^2$
= 9.09 kN total.

* SO USE LEVEL MASTER CENTRE LOADED ADJUSTABLE TOP/POST HEAD
BECAUSE: $35.7 \text{ kN} < 150 \text{ kN}$
AND $9.09 \text{ kN} < 13 \text{ kN}$.

0.42

CAP TO COLUMN CONNECTION TO HAVE 4/12g SCREWS (2 each opp face). UNLESS FIXING TO EXISTING COLUMNS AS PER EXISTING COLUMN TABLE.

* ALL SCREWS TO BE CLASS 4
12g (24TPI) FROM ICCONS PTY LTD.

* IF NOT CENTRALLY LOADED ALL UPLIFT LOADS ARE 13.0 kN

* IF NOT CENTRALLY LOADED ALL DOWNWARDS LOADS ARE 13.0 kN

* ALL STEEL TO BE G250 (U.N.O).

J

200mm x 75mm x 10mm
STRAIGHT
MAX UPLIFT = 72.0 kN
MAX DOWNWARDS LOAD = 150 kN

200mm x 75mm x 10mm
STRAIGHT (offset holes)
MAX UPLIFT = 72.0 kN
MAX DOWNWARDS LOAD = 150 kN

200mm x 150mm x 12mm
STRAIGHT (4 holes)
MAX UPLIFT = 72.0 kN
MAX DOWNWARDS LOAD = 150 kN

200mm x 220mm x 12mm
LARGE STRAIGHT (4 holes)
MAX UPLIFT = 72.0 kN
MAX DOWNWARDS LOAD = 150 kN

140mm x 75mm x 10mm
END OF BEARER
MAX UPLIFT = 72.0 kN
MAX DOWNWARDS LOAD = 150 kN

200mm x 75mm x 12mm
END SLOTTED
MAX UPLIFT = 72.0 kN
MAX DOWNWARDS LOAD = 150 kN

101mm x 155mm x 75mm
VERTICAL PLATE STIRRUP
MAX UPLIFT = 72.0 kN
MAX DOWNWARDS LOAD = 150 kN
* CENTRALLY LOADED

150mm x 150mm x 10mm
VERTICAL LARGE CORNER (8 holes)
MAX UPLIFT = 72.0 kN
MAX DOWNWARDS LOAD = 150 kN

150mm x 150mm x 10mm
CORNER
MAX UPLIFT = 72.0 kN
MAX DOWNWARDS LOAD = 150 kN

125mm x 140mm x 80mm
VERTICAL PLATE (large)
MAX UPLIFT = 72.0 kN
MAX DOWNWARDS LOAD = 150 kN
* CENTRALLY LOADED

90mm x 90mm x 10mm
VERTICAL PLATE 90
MAX UPLIFT = 72.0 kN
MAX DOWNWARDS LOAD = 150 kN
* CENTRALLY LOADED

225mm x 150mm x 10mm
TEE
MAX UPLIFT = 72.0 kN
MAX DOWNWARDS LOAD = 150 kN

150mm x 150mm x 10mm
CORNER (4 holes)
MAX UPLIFT = 72.0 kN
MAX DOWNWARDS LOAD = 150 kN

106mm x 80mm x 56mm
VERTICAL PLATE (small)
MAX UPLIFT = 72.0 kN
MAX DOWNWARDS LOAD = 150 kN
* CENTRALLY LOADED

225mm x 180mm x 90mm
VERTICAL PLATE (xlarge)
MAX UPLIFT = 72.0 kN
MAX DOWNWARDS LOAD = 150 kN
* CENTRALLY LOADED

95mm x 57mm x 20mm
CONTAINER LOCK - CL
MAX UPLIFT = 72.0 kN
MAX DOWNWARDS LOAD = 150 kN
* CENTRALLY LOADED

52mm x 100mm x 80mm
VERTICAL PLATE STIRRUP
MAX UPLIFT = 72.0 kN
MAX DOWNWARDS LOAD = 150 kN
* CENTRALLY LOADED

NETT WIND PRESSURE AT STUMP (kN/m²)						
WIND CLASS	N2	N3	N4	C1	C2	C3
UPWARDS	-	1.01	1.82	1.20	2.10	3.80
DOWNWARDS	0.41	0.64	1.15	0.76	1.32	2.39

EXAMPLE:-
* LEVEL MASTER STUMP SUPPORTING 9m² OF ROOF LOAD AND 9m² OF FLOOR LOAD 3m OF WALL FRAME 2.4m HIGH IN AN N3 WIND AREA.

EXAMPLE WORKINGS:-
DOWNWARDS=9m² x 0.78kN/m² (roof) +
9m² x 2.85kN/m² (floor) +
3m wall x 2.4 high x 0.42kN/m² (wall)
= 35.7 kN total.

N3 WIND UPLIFT= 9m² x 1.01kN/m²
= 9.09 kN total.

* SO USE LEVEL MASTER CENTRE LOADED ADJUSTABLE TOP/POST HEAD BECAUSE: 35.7 kN < 150 kN AND 9.09 kN < 13 kN.

TYPICAL LOADS (kN/m²)	
DOMESTIC FLOOR	2.85
SHEET ROOF	0.78
CLAD WALLS	0.42




CAP TO COLUMN CONNECTION TO HAVE 8/12g SCREWS (equally spaced).


















* ALL SCREWS TO BE CLASS 4 12g (24TPI) FROM ICCONS PTY LTD.

* IF NOT CENTRALLY LOADED ALL UPLIFT LOADS ARE 13.0 kN

* IF NOT CENTRALLY LOADED ALL DOWNWARDS LOADS ARE 13.0 kN

* ALL STEEL TO BE G250 (U.N.O).

DRAWING REVISIONS				REFERENCE DRAWINGS		COPYRIGHT THESE DESIGNS, PLANS AND INFORMATION ARE COPYRIGHT AND ARE NOT TO BE USED OR REPRODUCED WHOLLY OR IN PART OR TO BE USED ON ANY PROJECT WITHOUT THE WRITTEN PERMISSION OF SUMMERMORE PTY LTD DO NOT SCALE FROM THESE DRAWINGS.	SIGNED APPROVAL			<div>Summermore Pty Ltd Consulting Engineers ACN: 108 888 433 ABN: 42 108 888 433 ron@summermore.com.au www.summermore.com.au PO Box 1671 Browns Plains BC, QLD, 4118 Phone: 07 3800 0973 Fax: 07 3800 1860</div> <div></div>	CLIENT	PROJECT		
J	REVISED AS PER CLIENTS REQUEST	GAB	AUG2022				APPROVED		19SEP2022			ADJUSTABLE POST HEADS		
I	REVISED AS PER CLIENTS REQUEST	GAB	MAR2021				RPEQ	6715				TITLE Screw On Connectors CHS Capacities		
H	REVISED AS PER CLIENTS REQUEST	GAB	FEB2021				REVIEWED							
G	REVISED AS PER CLIENTS REQUEST	RAB	OCT2020				DESIGNED	RAB	AUG 2022			 Stronger • Easier • Faster ADJUSTABLE HOUSE STUMPS	DRAWING NUMBER	REV
F	REVISED AS PER CLIENTS REQUEST	GAB	APR2019				DRAWN	GAB	AUG 2022					
-	PRELIMINARY FOR CLIENTS APPROVAL	GAB	MAY2016				SCALE	AS SHOWN						
REV	DESCRIPTION	BY	DATE	DRAWING NAME	TITLE	ORIGINAL DRAWING SIZE at A3					16-10897-S04	J		



NETT WIND PRESSURE AT STÜMP (kN/m)						
WIND CLASS	N2	N3	N4	C1	C2	C3
UPWARDS	-	1.01	1.82	1.20	2.10	3.80
DOWNWARDS	0.41	0.64	1.15	0.76	1.32	2.39



TYPICAL LOADS (kN/m²)	
DOMESTIC FLOOR	2.85
SHEET ROOF	0.78
CLAD WALLS	0.42

CAP TO COLUMN CONNECTION TO BE WELDED ON ALL 4 EDGES.


* IF NOT CENTRALLY LOADED ALL UPLIFT LOADS ARE 13.0 kN

* IF NOT CENTRALLY LOADED ALL DOWNWARDS LOADS ARE 13.0 kN


* ALL STEEL TO BE G250 (U.N.O.).

DRAWING REVISIONS				REFERENCE DRAWINGS		COPYRIGHT THESE DESIGNS, PLANS AND INFORMATION ARE COPYRIGHT AND ARE NOT TO BE USED OR REPRODUCED WHOLLY OR IN PART OR TO BE USED ON ANY PROJECT WITHOUT THE WRITTEN PERMISSION OF SUMMERMORE PTY LTD DO NOT SCALE FROM THESE DRAWINGS.	SIGNED APPROVAL			<div>Summertime Pty Ltd Consulting Engineers</div> <div>ACN: 108 888 433 ABN: 42 108 888 433 ron@summertime.com.au www.summertime.com.au</div> <div>PO Box 1671 Browns Plains BC, QLD, 4118 Phone: 07 3800 0973 Fax: 07 3800 1860</div> <div></div>	CLIENT		PROJECT	
J	REVISED AS PER CLIENTS REQUEST	GAB	AUG2022				APPROVED		19SEP2022		ADJUSTABLE POST HEADS			
I	REVISED AS PER CLIENTS REQUEST	GAB	MAR2021				RPEQ	6715			TITLE			
H	REVISED AS PER CLIENTS REQUEST	GAB	FEB2021				REVIEWED				Weld On Connectors SHS Capacities			
G	REVISED AS PER CLIENTS REQUEST	RAB	OCT2020				DESIGNED	RAB	AUG 2022		DRAWING NUMBER			
F	REVISED AS PER CLIENTS REQUEST	GAB	APR2019				DRAWN	GAB	AUG 2022		REV			
-	PRELIMINARY FOR CLIENTS APPROVAL	GAB	MAY2016				SCALE	AS SHOWN			16-10897-S05			
REV	DESCRIPTION	BY	DATE	DRAWING NAME	TITLE		ORIGINAL DRAWING SIZE at A3							

* IF NOT CENTRALLY LOADED ALL
DOWNWARDS LOADS ARE 13.0 kN




35mm SLEEVE
LENGTH




SUIT 75mm & 89mm POST
CAST IN BASEPLATE
TO CONCRETE

MAX UPLIFT = 36.0 kN



90mm SLEEVE
LENGTH



SUIT 75mm, 89mm & 100mm POST - 4 holes
BOLT DOWN BASEPLATE
(4 HOLES)


MAX UPLIFT = 36.0 kN

BOLT DOWN OPTIONS (4 HOLES) - 20MPa concrete (min) - 90mm edge distance (min)


RAMSET CHEMSET '101'	4 x M12-100 CHEMSETS (1 x each corner)
WERCS ANKASCREW	4 x M12-60 WERCS ANKASCREWS (1 x each corner)

TYPICAL LOADS (kN/m ²)	
DOMESTIC FLOOR	2.85
SHEET ROOF	0.78
CLAD WALLS	0.42

NETT WIND PRESSURE AT STUMP (kN/m ²)						
WIND CLASS	N2	N3	N4	C1	C2	C3
UPWARDS	-	1.01	1.82	1.20	2.10	3.80
DOWNWARDS	0.41	0.64	1.15	0.76	1.32	2.39



90mm SLEEVE
LENGTH



SUIT 75mm, 89mm & 100mm POST
BOLT DOWN BASEPLATE
(2 HOLES)

MAX UPLIFT = 36.0 kN

BOLT DOWN OPTIONS (2 HOLES) - 20MPa concrete (min) - 90mm edge distance (min)

RAMSET CHEMSET '101'	2 x M12-200 CHEMSETS (1 x each side)
WERCS ANKASCREW	2 x M12-90 WERCS ANKASCREWS (1 x each side)

* 89SHS3.5 or 100SHS4.0 COLUMN MAXIMUM COMPRESSION
LOAD EXCEEDS 150kN UP TO 4500mm HEIGHT.

* 75SHS3.0 COLUMN MAXIMUM COMPRESSION
LOAD EXCEEDS 150kN UP TO 2500mm HEIGHT.

* 75SHS4.0 COLUMN MAXIMUM COMPRESSION
LOAD EXCEEDS 150kN UP TO 3000mm HEIGHT.

* ALL OTHER COLUMNS/HEIGHTS TO BE SITE SPECIFIC DESIGNED.

COLUMN TO BASEPLATE CONNECTION TO
HAVE 4/12g SCREWS (2 each opp face).

EXAMPLE:-



* LEVEL MASTER STUMP SUPPORTING 9m² OF ROOF LOAD AND 9m² OF
FLOOR LOAD 3m OF WALL FRAME 2.4m HIGH IN AN N3 WIND AREA.

EXAMPLE WORKINGS:-

DOWNWARDS=9m² x 0.78kN/m² (roof) +
9m² x 2.85kN/m² (floor) +
3m wall x 2.4 high x 0.42kN/m² (wall)
= 35.7 kN total.

N3 WIND UPLIFT= 9m² x 1.01kN/m²
= 9.09 kN total.

* SO USE LEVEL MASTER CENTRE LOADED ADJUSTABLE TOP/POST HEAD
BECAUSE: 35.7 kN < 150 kN
AND 9.09 kN < 13 kN.

DRAWING REVISIONS				REFERENCE DRAWINGS		COPYRIGHT THESE DESIGNS, PLANS AND INFORMATION ARE COPYRIGHT AND ARE NOT TO BE USED OR REPRODUCED WHOLLY OR IN PART OR TO BE USED ON ANY PROJECT WITHOUT THE WRITTEN PERMISSION OF SUMMERMORE PTY LTD DO NOT SCALE FROM THESE DRAWINGS.	SIGNED APPROVAL			<div>Summermore Pty Ltd Consulting Engineers ACN: 108 888 433 ABN: 42 108 888 433 ron@summermore.com.au www.summermore.com.au PO Box 1671 Browns Plains BC, QLD, 4118 Phone: 07 3800 0973 Fax: 07 3800 1860</div> <div></div>	CLIENT		PROJECT	
J	REVISED AS PER CLIENTS REQUEST	GAB	AUG2022				APPROVED		19SEP2022		ADJUSTABLE POST HEADS			
I	REVISED AS PER CLIENTS REQUEST	GAB	MAR2021				RPEQ	6715			TITLE Base Plates SHS Capacities			
H	REVISED AS PER CLIENTS REQUEST	GAB	FEB2021				REVIEWED							
G	REVISED AS PER CLIENTS REQUEST	RAB	OCT2020				DESIGNED	RAB	AUG 2022					
F	REVISED AS PER CLIENTS REQUEST	GAB	APR2019				DRAWN	GAB	AUG 2022					
-	PRELIMINARY FOR CLIENTS APPROVAL	GAB	MAY2016				SCALE	AS SHOWN			DRAWING NUMBER		REV	
REV	DESCRIPTION	BY	DATE	DRAWING NAME	TITLE		ORIGINAL DRAWING SIZE at A3				16-10897-S06		J	

